

QUARTZ STYLE

20MM EXTERNAL LEVATO MONO PAVER

3 **COLOURS**





- Quartz Style is a range interpreting natural quartzite, offering gently varying shades and distinctive stone markings.
- Textured surface.
- Available in a 10mm thickness for indoor coordination.









COLOURS •







Variation

Please Note: Tones in these images are indicative. Real samples can be requested for free.

TECHNICAL INFORMATION





Please Note: All sizes are nominal. If required, please contact us for exact working sizes. All porcelain tiles have rectified edges.

BREAKING STRENGTH	ISO 10545 - 4	>13.000N	
POINT LOAD	EN 12825	CENTRE SIDE CENTRE DIAGONAL	600x600 6,87kN 4,61kN 6,44kN
RESISTANCE TO ABRASION	ISO 10545 - 6	<150mm ³	

For a Raised Installation: Required pedestal positions based on size.



Please Note: For voids in excess of 100mm, Surface 360 recommends using our paving, in all affected areas.

Impact Control Membrane (ICM). To be applied to the underside of

SURFACE 360

QUARTZ STYLE

10MM INTERNAL LEVATO PORCELAIN TILE

COLOURS





- Quartz Style is a range interpreting natural quartzite, offering gently varying shades and distinctive stone markings.
- · Natural and polished surface finishes available.
- Available in a 20mm thickness for outdoor coordination.
















Please Note: Tones in these images are indicative. Real samples can be requested for free.

TECHNICAL INFORMATION

				Sizes:	
	FORMAT SIZE	FINISH	THICKNESS	SLIP RESISTANCE	
					300 x 300
1	300 x 300	Natural	10mm	R10 (B)	
2	300 x 600	Natural	10mm	R10 (B)	300 x 600
	300 x 600	Polished	10mm		
3	600 x 600	Natural	10mm	R10 (B)	
	600 x 600	Polished	10mm	, (=)	600 x 600
	000 11 000				

Please Note: All sizes are nominal. If required, please contact us for exact working sizes. All porcelain tiles have rectified edges.

• www.surface360.co.uk