



Eterno Ivica Levato™ Fixed Head Pedestal system has a height range of 25mm to 270mm.

With a choice of 5 Pedestal sizes, the bi-component fixed head has an anti-noise and anti-slip rubber support section.

Pedestals are comprised of a cylindrical base element of 205mm diameter, an intermediate screw with a locking security system, and a support head element with 4 snap-off tabs of h.12mm in 4mm thickness.

The base is provided with holes for water drainage and 4 pre-cut lines to facilitate any cutting of the base, if required. The adjustment of height is achieved using a specialised height adjustment key.



NM1
25-40mm

NM2
40-70mm

NM3
60-100mm

NM4
90-160mm

NM5
150-270mm

Characteristics	Adjustable in height Fixed head Regulation key for height adjustment Snap off tabs Security lock system
Raw Material	Bicomponent material (PP and rubber), main body and Base (PP)
Environmental Impact	Recyclable Product - Inert
Application Surfaces	Any waterproofing membrane, or solid surface - surface must be suitable for combined weight of paving and support systems
Applications	Exterior flooring

Characteristics	Unit	Value	Tolerance
Base Diameter	mm	205	+/- mm 1.0
Base Thickness	mm	5	+/- mm 0.2
Head Diameter	mm	110	+/- mm 0.8
Base Surface Area	cmq	330	+/- cmq 5
Tabs Thickness	mm	4	+/- mm 0.2
Tabs Height	mm	12	+/- mm 0.2

Central Compression Loading Limit Resistance*

(calculated at medium highness, between minimum and maximum extension)

Eccentric Compression Loading Limit Resistance*

(calculated at medium highness, between minimum and maximum extension)



	Min Height (mm)	Max Height (mm)	Central Loading Limit (KN)	Eccentric Loading Limit (KN)
NM1	25	40	31.18	15.19
NM2	40	70	38.67	21.48
NM3	60	100	46.53	26.07
NM4	90	160	29.57	16.75
NM5	150	270	28.60	18.89

* 1 KN = 98.6 Kg

	Unit	Value
Shore	Shore d	70 (+/- 3)

Physical Properties	Method	Unit	Value
Fire Reaction	UNI EN 13501-1:2009	Class	E
Low Temperatures Reaction			-40°

The above data is relevant to current production and may be changed or updated by Surface 360 (The Deck Tile Co) at any time without notice.

Given the many possible uses and the possible interference of external elements, we do not assume responsibility for the results.

The buyer is required to establish under their own responsibility the suitability of the product for the intended use.

This document is property of Surface 360 (The Deck Tile Co). All rights reserved.